

# Carbon Monoxide Monitor Comparison

|   | UL Listed Alarms | Other Low Level Monitors | NSI 3000 Low Level Monitor |
|---|------------------|--------------------------|----------------------------|
| Professional grade sensor                             |                  | ● <sup>2</sup>           | ●                          |
| 1st visual readout at 5 ppm within 30 seconds         |                  |                          | ●                          |
| Low audible alarm level at 15 ppm after 5 minutes     |                  |                          | ●                          |
| High level audible alarm at 35 ppm after 5 minutes    |                  |                          | ●                          |
| Crisis audible alarm level at 70 ppm after 30 seconds | 1                | ●                        | ●                          |
| Manual silence button at low levels                   |                  | ●                        | ●                          |
| Cannot be silenced at crisis levels                   |                  |                          | ●                          |
| Protection for all ages                               |                  | ●                        | ●                          |
| Digital memory with recall                            | ● <sup>2</sup>   | ●                        | ●                          |
| Continuous on-screen display                          |                  |                          | ●                          |
| Digital CO readout                                    | ● <sup>2</sup>   | ●                        | ●                          |
| CO display range from 5-999 ppm                       |                  |                          | ●                          |
| Battery operated                                      | ● <sup>2</sup>   | ●                        | ●                          |
| Can be installed at eye level                         | ● <sup>2</sup>   | ●                        | ●                          |
| Can be converted to tabletop use                      |                  |                          | ●                          |
| Sensor can be checked with match smoke                |                  | ●                        | ●                          |
| User response instructions printed on unit            |                  |                          | ●                          |
| Minimum 3-year warranty                               | ● <sup>2</sup>   |                          | ●                          |
| Maximum protection for all age groups                 |                  |                          | ●                          |

Notes:

ppm = parts per million

1 - Allowed to take up to 240 minutes to alarm

2 - Available only on a few models